



Xyron® machines are your complete professional document finishing system. Instantly applies laminate, adhesive or both without heat or electricity. Perfect for presentations, comps, mock ups, posters, signs, and displays.

9"



12"



25"



44"



63"



FEATURES



Cold Lamination

Aggressive adhesive paired with high pressure rollers allows items to be trimmed right to the edge, without peeling or lifting.



No Heat or Mess

Instantly bonds with no warm-up time, or overspray.



Environmentally Safe

Acid-free, non-toxic without the need for spray booths or vents.



Edge-to-Edge

Apply to items up to 63 inches wide for full coverage.

MACHINE**SPECS****REFILLS****624672****Footprint** — 13" x 6.75" x 5"**Weight/Packed Weight** —
5 lbs (2.27kg)**Document Thickness**
(max.) — 0.10" Up to 3/16"**Finished Document Width**
(max.) — 8.5"**Trimming** — Replaceable cutter**145612** - 2 sided laminate 8.5" x 60'**624674** – 2 sided laminate 5" x 18'**100128** – 1 Side Laminate/1 Side Magnet 8.5" x 10'**XM1255****Footprint** — 10.5" x 13" x 15"**Weight/Packed Weight** —
14.75lbs (6.6kg) / 18.25lbs (8.2kg)**Document Thickness**
(max.) — 0.125"**Finished Document Width**
(max.) — 11.75"**Trimming** — Replaceable cutter**AT1251-100** High Tack Adhesive
12"/100'**AT1255-100** Permanent
Standard Adhesive 12"/100'**AT1256-100** Repositionable
Adhesive 12"/100'**DL1251-150** 2-Sided Standard
Use Laminate 12"/150'**LAT1251-100** 1 Side Laminate/1
Side High Tack Adhesive
12"/100'**LAT1256-100** 1 Side Laminate/1
Side Repositionable Adhesive
12"/100'**100080** Single Sided Laminate,
12"/150'**XM2500****Footprint** — 18.5" x 28.125" x 15"**Weight/Packed Weight** —
57lbs (25.9kg) / 72lbs (32.7kg)**Document Thickness**
(max.) — 0.10" Up to 3/16" foam core**Finished Document Width**
(max.) — 25" (63.5cm)**Trimming** — Replaceable cutter**AT400-300** High Tack Adhesive
24.9"/300'**AT405-300** Permanent Standard
Adhesive 24.9"/300'**AT406-170** Repositionable
Adhesive 24.9"/170'**DL403-300** 2-Sided Standard
Use Laminate 25.3"/300'**DL404-300** 2-Sided Thermal
Print Sensitive Laminate
24.9"/300'**LAT405-300** 1 Side Laminate/1
Side High Tack Adhesive
25.3"/300'**LAT409-150** 1 Side Laminate/1
Side Repositionable Adhesive
25.3"/150'**100081** Single Sided Laminate
25"/300'**XM4400****Footprint** — 50.5" x 11" x 14.5"**Weight/Packed Weight** —
155lbs (70kg) / 200lbs (91kg)**Document Thickness**
(max.) — 0.10" Up to 3/16"**Finished Document Width**
(max.) — 42"**Trimming** — Replaceable cutter**AT4301-300** High Tack
Adhesive 42"/300'**AT4306-170** Repositionable
Adhesive 42"/170'**DL3800-300** 2-Sided Standard
Use Laminate 38"/300'**100082** Single Sided Laminate
43"/300'**DL4300-300** 2-Sided Standard
Use Laminate 2"/300'**DL3802-300** 2-Sided Thermal
Print Sensitive Laminate
38"/300'**LAT3801-300** 1 Side Laminate/1
Side High Tack Adhesive
38"/300'**LAT4301-300** 1 Side Laminate/1
Side High Tack Adhesive 2"/300'**LAT409-150** 1 Side Laminate/1
Side Repositionable Adhesive
25.3"/150'**100108****Footprint** — 79.8" x 21.7" x 54.7"**Weight** — 322 lbs**Document Thickness** — .8"**Finished Document Width** —
up to 63"**CONTACT YOUR LOCAL DEALER**